



Product Information Sheet

Material Safety Data Sheet (MSDS) also available

www.revqlp.net



Product : SAE 15W-40

Part # : R912 (1 L), R914 (4 L)

Type : Engine Oil

Engine : Diesel

Description : Heavy Duty Diesel Engine Oil

Problem Symptom

REV SAE 15W-40 was developed for today's modern diesel engines, equipped with EGR valves in highway tractors, off-road diesel powered equipment and diesel powered passenger vehicles.

Performance

- Formulated to protect against viscosity and thermal breakdown
- It's high 9 TBN combined with its greater oxidation stability promote extended oil drains
- Specifically designed for running with high or low sulphur diesel fuels

Application

Refer to owner's manual for engine specifications and fill capacities.

Characteristics

Will meet or exceed the following performance requirements

- API CI-4, CH-4, CG-4, CF-4, CF-SL
- ACEA E5-99 & E3-96
- Global DHD-1, Mercedes Benz 228.3
- Cummings CES 20078
- Ford, Navistar, GM, John Deere, Caterpillar, Detroit Diesel, Chrysler, MAN, Allison C4
- Mack EO-M, EO-M Plus, EO-M Premium Plus, EO-L, EO-L Plus
- Volvo VDS-2

Packaging

1L	12 bottles per case	72 cases per skid	25 Lbs. / Case
4 L	4 bottles per case	50 cases per skid	35 Lbs. / Case
20 L	Drum	39 pails per skid	41 Lbs. / Pail
205 L	Drum	4 drums per skid	435 Lbs. / Drum