



# Product Information Sheet

Material Safety Data Sheet (MSDS) also available

[www.revqlp.net](http://www.revqlp.net)



<b>Product</b>	: TDH
<b>Part #</b>	: R660, R660D
<b>Type</b>	: Hydraulic Fluid AW
<b>Engine</b>	: N/A
<b>Description</b>	: Trans. Diff. Hydraulic

Prolongs the life of the hydraulic system  
Reduces maintenance costs

## Problem Symptom

Trans-Hydraulic Fluid is a multi-purpose fluid for farm and industrial applications requiring a common transmission/differential/hydraulic fluid. It meets and exceeds the performance requirements of all original equipment manufacturers. This includes John Deere J20C, Ford ESN-M2C134-D, Massey M-1135/1141, JI Case MS-1207.

## Performance

- Contains a demulsifying additive to quickly separate water. Resists rust, corrosion and oxidation. Remains stable even when exposed to humidity and extreme temperatures.
- Contains zinc type anti-wear agents to help minimize the wear and tear on high speed and high pressure hatch system and on gear and piston pumps.
- Contains anti-foaming agents to help control the air evacuation. Compatible with filters sold on the market.

PROPERTIES	SAE GRADE	20W-50
Density, Kg/m3 @ 15°C (60°F)		872
Pound per U.S. Gallon 15°C (60°F)		7.26
cP @ -20°C (Brookfield)		58.9
cp @ -35°C (Brookfield)		9.4
cSt @ 40°C		4,000
cSt @ 100°C		53,400
SUS @ 100°F		234 (454)
SUS @ 210°F		2.5
Viscosity Index (D2270)		1B
Flow Point, °C (°F)		301
Flash Point (COC), °C (°F)		57.9
Colour (D1500)		139
Copper Strip Corrosion (D130)		-40 (-40)
Sulfated Ash (D874), wt. %		1.42
Total Base Number (D289)		9.7
Zinc, wt. %		0.15

## Packaging

20L	Pail	48 Pails per Pallet	41 Lbs. each
205 L	Drum	4 Drums per Pallet	435 Lbs. each